DRIVENETS

DATASHEET

OPTICAL TRANSCEIVER · OSFP112 RIDING HEAT SINK

DriveNets 800G 2×VR4

OSFP112 transceiver with dual MPO-12 interfaces and a riding heat sink, delivering 8 × 106.25 Gbps PAM4 at 850 nm over multimode fiber for short-reach 800GbE and AI cluster interconnect.

800 Gbps

AGGREGATE LINE RATE

8 × 106.25G PAM4

Dual MPO-12 · 50 m MMF

16 W maximum



OVERVIEW

The DriveNets 800G OSFP112 2×VR4 is an octal small-form-factor, hot-pluggable optical transceiver that transmits and receives serial optical data at up to 106.25 Gbps per channel using PAM4 modulation over multimode fiber. Eight 53.125 GBd electrical lanes map to eight VCSEL-driven optical lanes at 840 - 870 nm presented on a dual MPO-12 interface, giving 800 Gbps of aggregate capacity at reaches up to 50 m over multimode fiber. The module integrates high-performance VCSELs, a PAM4 DSP and a riding heat sink (RHS) in an OSFP112 form factor, and is compliant with 800G Ethernet specifications - IEEE Std 802.3db-2022 and IEEE Std 802.3ck-2022 - the OSFP MSA rev 5.0 and OIF-CMIS 5.2 management. Maximum power consumption is 16 W across a +25 °C to +70 °C case-temperature range, suiting 800GbE switch and router connections, datacenter and AI cluster fabrics, and other 800G / 400G interconnect requirements.

Optical interface

Dual MPO-12 · 8 lanes at 106.25 Gbps PAM4

840 - 870 nm VCSEL · 50 m over multimode fiber

Class 1 laser product per IEC 60825-1

Electrical & management

60-contact edge connector · 8 × 53.125 GBd host lanes

2-wire serial (SCL / SDA) · OIF-CMIS 5.2 memory map

IEEE 802.3ck-2022 host electrical compliance

Power & environmental

16 W maximum power consumption

+25 °C to +70 °C case · riding heat sink (RHS)

RoHS II 2011/65/EU · digital diagnostics monitoring

HARDWARE SPECIFICATION

Key specifications

Ordering & package

Part number	**DNOT00012**
Form factor	**OSFP112 RHS**
Optical interface	**Dual MPO-12, multimode**
Data rate	**800G (8 × 106.25 Gbps PAM4)**
Reach	**50 m multimode fiber**

Electrical

Supply voltage (VCC)	**3.135 – 3.465 V**
Baud rate per lane	**53.125 GBd ±100 ppm**
Power consumption	**16 W maximum**
Input voltage tolerance	**750 mVpp**
Output voltage, short mode	**600 mVpp max**
Eye height / VEC	**15 mV min / 12 dB max**

Optical – transmitter

Modulation format	**PAM4**
Center wavelength	**840 – 870 nm (850 nm typ.)**
Output power (PAVG)	**-4.6 to 4 dBm**
Extinction ratio	**2.5 dB min**
Off-transmitter launch power	**-30 dBm max**
OMAouter, max(TECQ, TDECQ) ≤ 1.8 dB	**-2.6 to 3.5 dBm**

Environmental

Operating case temp	**+25 °C – +70 °C**
Storage temperature	**-40 °C – +85 °C**
Relative humidity	**5% – 85%**
VCC absolute maximum	**-0.3 V – +3.6 V**
Cooling	**Riding heat sink (RHS)**

Optical – receiver


Average receive power	**-6.3 to 4 dBm**
Sensitivity (OMAouter)	**-4.4 dBm @ 2.4E-4**
Stressed sensitivity	**-1.8 dBm**
Receive power (OMAouter)	**3.5 dBm max**
Damage threshold	**5 dBm per lane**

Management & DDM

Host interface	**60-contact edge connector**
Memory map	**OIF-CMIS 5.2**
Temperature / voltage	**±3 °C / ±0.1 V**
Tx bias current, per lane	**±10%**
Tx / Rx power, per lane	**±3 dB**

INTERFACE OVERVIEW

Module layout



REGULATORY COMPLIANCE

Certifications

EMC

FCC 47 CFR Part 15, Class B

EN 55032:2015+A11:2020+A1:2020

EN 55035:2017+A11:2020

IEC 61000-4-3:2020

IEC EN 61000-4-2:2008

Product safety

CB: IEC 62368-1:2018

TÜV Mark: EN IEC 62368-1:2020+A11

UL Recognized Component: UL 62368-1:2019 R10.21, CSA C22.2 No. 62368-1:19

Optical & environmental

Class 1 laser product

FDA/CDRH

IEC 60825-1:2014

IEC 60825-2:2021

EN 60825-1:2014+A11

Complies with RoHS II Directive 2011/65/EU

800 Gbps
AGGREGATE LINE RATE

8 × 106G
PAM4 LANES

50 m
REACH OVER MMF

16 W
MAXIMUM POWER

APPLICATIONS & STANDARDS

Applications

- 800GBASE Ethernet
- Switch & router connections
- Datacenters & AI clusters
- Other 800G / 400G interconnect requirements

Reference documents

- OIF-CMIS-05.2 - common management interface specification (CMIS) rev 5.2
- OSFP MSA specification for OSFP octal small form factor pluggable module rev 5.0
- IEEE Std 802.3db™-2022
- IEEE Std 802.3ck™-2022

RATINGS

Absolute maximum ratings

PARAMETER	SYMBOL	MIN	MAX	UNIT
Storage temperature range	T_S	**-40**	**+85**	°C
Relative humidity	RH	**5**	**85**	%
Power supply voltage	V_{CC}	**-0.3**	**+3.6**	V
Rx damage threshold, per lane			**5**	dBm

1. Absolute maximum ratings: modules operated outside this range may be permanently damaged.

OPERATING CONDITIONS

Recommended operating conditions

PARAMETER	SYMBOL	MIN	TYPICAL	MAX	UNIT
Operating case temperature	T_C	**25**	**-**	**70**	°C
Power supply voltage	V_{CC}	**3.135**	**3.3**	**3.465**	V
Baud rate, per channel	BR	**53.125 -100 ppm**	**53.125**	**53.125 +100 ppm**	GBd

1. Recommended operating conditions: performance is not guaranteed outside this range.

MONITORING

DDM accuracy

PARAMETER	ACCURACY	UNIT	CALIBRATION
Temperature	**±3**	°C	Internal
Voltage	**±0.1**	V	Internal
Tx bias current, each lane	**±10**	%	Internal
Tx output power, each lane	**±3**	dBm	Internal
Rx receive power, each lane	**±3**	dBm	Internal

MANAGEMENT

Memory map

Refer to OIF-CMIS - common management interface specification (CMIS).

Optical characteristics

The following optical characteristics are defined over the recommended operating conditions unless otherwise specified.

PARAMETER	SYMBOL	MIN	TYPICAL	MAX	UNIT	NOTES
Transmitter (each lane)						
Signaling speed per lane		**53.125 -100 ppm**	**53.125**	**53.125 +100 ppm**	GBd	
Modulation format	MF		**PAM4**			
Center wavelength		**840**	**850**	**870**	nm	
RMS spectral width	RMS			**0.65**	nm	
Average launch power per lane	P_{AVG}	**-4.6**		**4**	dBm	1
Outer optical modulation amplitude, max (TECQ, TDECQ) ≤ 1.8 dB	OMA_{outer}	**-2.6**		**3.5**	dBm	
Outer optical modulation amplitude, 1.8 < max (TECQ, TDECQ) ≤ 4.4 dB	OMA_{outer}	**-4.4 + max (TECQ, TDECQ)**		**3.5**	dBm	
Transmitter excursion, each lane				**2.3**	dB	
Extinction ratio	ER	**2.5**			dB	
Transmitter and dispersion penalty eye closure for PAM4	TDECQ			**4.4**	dB	
Transmitter transition time	T_r, T_f			**17**	ps	
$RIN_{14}OMA$				**-132**	dB/Hz	
Encircled flux	FLX		**≥ 86% at 19 µm** **≤ 30% at 4.5 µm**			
Optical return loss tolerance	ORL			**14**	dB	
Average launch power of OFF transmitter				**-30**	dBm	

PARAMETER	SYMBOL	MIN	TYPICAL	MAX	UNIT	NOTES
Receiver (each lane)						
Signaling speed per lane		**53.125 -100 ppm**	**53.125**	**53.125 +100 ppm**	GBd	
Modulation format	MF		**PAM4**			
Center wavelength		**840**	**-**	**870**	nm	
Damage threshold		**5**			dBm	
Average receive power per lane		**-6.3**		**4**	dBm	
Receive power, each lane (OMA_{outer})				**3.5**	dBm	
Receiver reflectance	RR			**-15**	dB	
Receiver sensitivity (OMA_{outer}), TECQ ≤ 1.8 dB				**-4.4**	dBm	2
Receiver sensitivity (OMA_{outer}), 1.8 < TECQ ≤ 4.4 dB				**-6.2 + TECQ**	dBm	2
Stressed receiver sensitivity (OMA_{outer})	SRS			**-1.8**	dBm	2
Conditions of the stressed receiver sensitivity test						
Stressed eye closure for PAM4 (SECQ), lane under test			**4.4**		dB	
OMA_{outer} of each aggressor lane			**3.5**		dBm	

1. Optical output power, each lane (min), is informative and not the principal indicator of signal strength.
2. Measured with conformance test signal at TP3 with BER = 2.4E-4.

ELECTRICAL

Electrical characteristics

The following electrical characteristics are defined over the recommended operating conditions unless otherwise specified.

PARAMETER	SYMBOL	MIN	TYPICAL	MAX	UNIT	NOTES
Supply voltage	V_{CC}	**3.135**		**3.465**	V	
Power consumption	PC			**16**	W	
Module input						
Differential peak-to-peak voltage tolerance		**750**			mV	TP1a
Peak-to-peak AC common-mode voltage tolerance, low-frequency	V_{CMLF}	**32**			mV	TP1a
Peak-to-peak AC common-mode voltage tolerance, full-band	V_{CMFB}	**80**			mV	TP1a
Differential-mode to common-mode return loss	RL_{cd}	See IEEE 802.3ck™, 120G.3.3.3			dB	TP1
Effective return loss	ERL	**8.5**			dB	TP1
Differential termination mismatch				**10**	%	TP1
Module stressed input tolerance		See IEEE 802.3ck™, 120G.3.4.3				TP1a
Single-ended voltage tolerance		**-0.4**		**3.3**	V	TP1a
DC common-mode voltage tolerance		**-0.35**		**2.85**	V	TP1
Module output						
Differential peak-to-peak output voltage, short mode				**600**	mV	TP4
Differential peak-to-peak output voltage, long mode				**845**	mV	TP4
Peak-to-peak AC common-mode voltage, low-frequency	V_{CMLF}			**32**	mV	TP4
Peak-to-peak AC common-mode voltage, full-band	V_{CMFB}			**80**	mV	TP4
Eye height		**15**			mV	TP4
Vertical eye closure	VEC			**12**	dB	TP4
Common-mode to differential-mode return loss	RL_{dc}	See IEEE 802.3ck™, 120G.3.1.1			dB	TP4
Effective return loss	ERL	**8.5**			dB	TP4
Differential termination mismatch				**10**	%	TP4
Transition time		**8.5**			ps	TP4
Common-mode voltage	V_{cm}	**-0.35**		**2.85**	V	TP4

PARAMETER	SYMBOL	MIN	TYPICAL	MAX	UNIT	NOTES
Low-speed signals - SCL and SDA (I_{OLmax} = 3 mA)						
Output low voltage	V_{OL}	**0**		**0.4**	V	
Output high voltage	V_{OH}	**V_{CC} - 0.5**		**V_{CC} + 0.3**	V	
Input low voltage	V_{IL}	**-0.3**		**V_{CC} × 0.3**	V	
Input high voltage	V_{IH}	**V_{CC} × 0.7**		**V_{CC} + 0.5**	V	

HOST INTERFACE

Pin assignment

The electrical interface of the OSFP module consists of a 60-pin contact edge connector, as illustrated in the figure below, which is defined in Clause 13.1 of the OSFP MSA Specification.




Figure 1. OSFP module pinout

SIGNALS

Pin description

NAME	PIN	DIRECTION	DESCRIPTION
TX[8:1]p / TX[8:1]n		Input	Transmit differential pairs from host to module.
RX[8:1]p / RX[8:1]n		Output	Receive differential pairs from module to host.
SCL	14	Bidirectional	2-wire serial clock signal. Requires pull-up resistor to 3.3 V on host.
SDA	47	Bidirectional	2-wire serial data signal. Requires pull-up resistor to 3.3 V on host.
LPWn/PRSn	17	Bidirectional	Multi-level signal for low-power control from host to module and module-presence indication from module to host.
INT/RSTn	44	Bidirectional	Multi-level signal for interrupt request from module to host and reset control from host to module.
VCC	15, 16, 45, 46	Power	3.3 V power for module.
GND		Ground	Module ground. Logic and power return path.

ARCHITECTURE

Functional block diagram




Figure 2. 800G OSFP 2xVR4 functional block diagram

COMPLIANCE

Regulatory and compliance

CATEGORY	STANDARD
EMC - immunity	EN 55035:2017+A11:2020 IEC 61000-4-3:2020
EMC - emission	FCC 47 CFR Part 15, Class B EN 55032:2015+A11:2020+A1:2020
ESD threshold	IEC EN 61000-4-2:2008
Product safety	CB: IEC 62368-1:2018 TÜV Mark: EN IEC 62368-1:2020+A11 UL Recognized Component: UL 62368-1:2019 R10.21, CSA C22.2 No. 62368-1:19
Optical safety	Class 1 laser product FDA/CDRH IEC 60825-1:2014 IEC 60825-2:2021 EN 60825-1:2014+A11
RoHS	Complies with RoHS II Directive 2011/65/EU

MECHANICAL

Mechanical package outline




Figure 3. Mechanical package outline (all dimensions are in mm) · Unit: mm. Unspecified tolerance: ±0.1 mm.

Optical interface




Figure 4. Optical lane sequence.
Note: optical interface is 8° APC dual MPO-12.